

Fastmark 400 Series

Maximum Performance – Minimum Expense



Fastmark 400 Desktop Thermal Printers – Full-Featured, Value-Priced

For your low to moderate printing applications, the Fastmark 400 Series offers all the advantages of large-label and tag printers at a fraction of the cost.

Built To Last

- Tough, high-impact ABS housing
- All-metal print mechanisms
- Advanced standard features and flexible options
- Supports rich fonts, full graphics, all popular linear barcodes and 2-D symbologies

Easy To Use

- No special operator training required
- Sleek clamshell design allows full accessibility for quick media and ribbon loading
- Unique “spring loaded release” feature offers print head replacement in seconds



FM 400 Series – Offering Standard Features Others Consider “Add-Ons”

- Label Design Software allows printing from PC and creating stand alone applications
- Windows™ Drivers included for 95/98/NT/2000
- Print speeds up to 3 inches per second and label lengths up to 45 inches
- 203dpi - 300dpi resolution for superior print quality, barcodes, text and graphics
- Serial and parallel interfaces
- Black Bar and Gap Sensor



PRINTER SPECIFICATIONS INCLUDE:

Models	FM402DT, FM402TT, FM403TT
Speed	FM402DT: 2 ips (51 mm/s) FM402TT: 3 ips (76 mm/s) FM403TT: 2 ips (51 mm/s)
Print Resolution	FM402DT and FM402TT: 203 dpi (8 dots/mm) FM403TT: 300 dpi (12 dots/mm)
Fonts	International character sets 5 alpha-numeric fonts from .049" - 0.23"H (1.25mm-6.0mm) All fonts expandable up to 24 x 24 4 direction 0° - 270° rotation Downloadable soft fonts
Graphics & Bar Codes	Code 39, Extended Code 39, Code 93, Code 128 UCC Code 128 (Subset A,B,C), Codabar, Interleave 2 of 5 EAN-8 2&5 add on, EAN-13, EAN-128, UPC, UPC-A E 2&5 add on, POSTNET, German POST, Matrix 25 Maxicode, PDF-417, PCX, BMP, GDI graphics
Print Width	FM402DT and FM402TT: 1.0" - 4.13" (25mm - 105mm) FM403TT: 1.0" - 4.25" (25mm - 108mm)
Print Method	FM402DT: Direct Thermal FM402TT and FM403TT: Direct Thermal and Thermal Transfer
Media Size	Max width 4.3" (110mm), Min width 1.0" (25mm) Min length 0.4" (10mm) Thickness .0025" ~ .01 (.0635mm ~ .245mm) Max roll capacity 4.3" (109mm) O.D. Core size 1.0" (25mm) I.D.
Media Type	Roll, die-cut, continuous, fan-fold, tags, ticket, thermal paper, plain paper, synthetics or foils
Indexing	Black Bar and Gap TOF
Ribbon	FM402TT and FM403TT: Wax, Wax/Resin, Resin Ribbon width - 1" - 4.3" (25mm - 109mm) Ribbon roll - max O.D. 1.4" (36mm) Core size 0.5" core I.D. (12.5mm) Ribbon length - 300' (91M)

Memory/Buffer	FM402DT and FM402TT: 512K standard, 512K expandable FM403TT: 2MB
Software	Windows Drivers (95/98/NT/2000) Label creation software included
Emulations	'A' and 'B' Industry Emulations
Interface	RS-232 serial, Centronics parallel
Network Interface	External QueMax II print server option
Physical/Electrical	W 7.3" X D 10.9" X H 6.0" (W186 X D278 X H153mm) FM402DT: 4.2 lbs. (1.9 kgs) FM402TT and FM403TT: 4.6 lbs. (21. Kgs.) 110/220 VAC ± 10%, 50/60 Hz CE, UL, CUL
Environmental	40°F ~ 100°F (4°C ~ 38°C) 10 ~ 90% non condensing FCC Class B emissions
Options	Cutter Peel and Present Flash memory card - 512K SRAM memory card - 512K Real time clock w/512K Flash Stand alone keyboard with LCD and format storage External 8" OD Media Stacker RS-232 cable
Warranty	One year Parts and Labor, Return to Depot Six months Printhead

All products are trademarks of their respective owners. Specifications are subject to change without notice. Some models and features may not be currently available.

Part No. 110023 Rev.*



Corporate Headquarters
4765 Calle Quetzal, Camarillo, CA 93012
(805) 388-5799 PH
(805) 484-5282 FX

Charlotte Operation
4216 Stuart Andrew Blvd., Charlotte, NC 28217
(704) 523-8500 PH
(704) 525-6104 FX

AMT Datasouth International
Unit B, Pinnacle 15, Gowerton Rd, Brackmills
Northampton, NN4 7BW, England
+44 1604 763394 PH
+44 1604 760661 FX

<http://www.amtdatasouth.com>